Title	NSW Marine Estate Towed Video Imagery		
Alternative title(s)	NSW Marine still imagery of the seabed for the NSW continental shelf		
Abstract	Raw downward facing still imagery of the seabed over the NSW continental shelf acquired using NSW government's (Department of Climate Change Energy Environment and Water) towed video system aboard RV Bombora. Acquisition is ongoing (>2015) predominantly funded by the department under Coastal Reform Climate Change Fund project 'State-wide Science' and/or by various collaborative agencies (DPI; Parks Australia; FRDC) and educational institutions (UoW: UTas). Imagery is captured over areas to 1) ground-truth seabed typologies and validate habitat boundaries derived from multi-beam echosounder (MBES) surveys (www.aodn.org.au or www.ausseabed.gov.au) and/or 2) habitat assessments and monitoring to capture broad distribution of seabed benthic communities. For biodiversity-type assessments, imagery is captured, and transects/sites are selected in a sampling design in accordance with the Australian Field Manuals for Marine Sampling. Imagery captured is generally of benthic habitats in 10-120m of water depth over the NSW inner shelf. Georeferenced (XYZ) and time-stamped (UTC) still imagery is accessible via SEED, the online annotation platform Squidle+ and SeaMap Australia.		
Resource locato	r		
<u>Data Quality</u> <u>Statement</u>	Name: Data Quality Statement Protocol: WWW:DOWNLOAD-1.0-httpdownload Description: Data quality statement for NSW Marine Estate Towed Video Imagery Function: download		
Unique resource	identifier		
Code	h91e1ded-8e6e-46d0-b690-eadf5d5b8816		
Presentation form	Image digital		
Edition	1		
Dataset language	English		
Metadata standa	ard		
Name	ISO 19115		
Edition	2016		
Dataset URI	https://datasets.seed.nsw.gov.au/dataset/b91e1ded-8e6e-46d0-b690-eadf5d5b8816		
Purpose	baseline for monitoring		
Status	Completed		
Spatial representation type	video		
Spatial reference system			
	-		

reference system	
Spatial resolution	1 m
Additional information source	Data were collected on 5-6 separate dates during the time period to acquire imagery once from each for the randomly selected locations identified at the start of the survey.
Topic category	

Keyword set	
keyword value	MARINE-Biology
	MARINE-Coasts
	MARINE-Reefs
	PHOTOGRAPHY-AND-IMAGERY-Remote-Sensing
Originating controlled vocabulary	
Title	ANZLIC Search Words
Reference date	2008-05-16
Geographic location	
West bounding longitude	152.303467
East bounding longitude	153.709717
North bounding latitude	-32.670304
South bounding latitude	-29.088277
NSW Place Name	Port Stephens Great Lakes
Vertical extent information	
Minimum value	-100
Maximum value	2228
Coordinate reference system	
Authority code	urn:ogc:def:cs:EPSG::
Code identifying the coordinate reference system	5711
Temporal extent	
Begin position	2019-10-20
End position	N/A
Dataset reference date	
Resource maintenance	
Maintenance and update frequency	Unknown
Contact info	
Contact position	Data Broker
Organisation name	NSW Department of Climate Change, Energy, the Environment and Water
Telephone number	131555
Email address	data.broker@environment.nsw.gov.au
Web address	https://www.nsw.gov.au/departments-and-agencies/dcceew
Responsible party role	pointOfContact

Lineage	Video surve for Marine S manuals-ma system and multibeam s Site/Docum procedures better than (horizontal) estimate 'fis coordinate of "Flag" colur validated by coordinates (JPG) and im annotation i	ying was undertaken following the recommendations detailed in 'Field Manuals Sampling to Monitor Australian Waters' (<u>https://www.nespmarine.edu.au/field- arine-sampling-monitor-australian-waters</u>). Details of the NSW DPIE towed video equipment are provided in 'SeaBed NSW: Standard Operating Procedures of surveying' (<u>https://www.environment.nsw.gov.au/-/media/OEH/Corporate- ents/Research/Our-science-and-research/seabed-nsw-standard-operating- -multibeam-surveying-190101.pdf</u>). XYZ positional accuracy of the still imagery is XY (3 degrees of slant range [eg. 2.6m radius @ 100m]; 2x ship's speed for XY and/or >2x cable speed for Z (vertical). Filtered coordinates were then used to sh' GPS location using the neighbouring average (3s time-step). Where a estimate was performed using one of these methods, the image's metadata nn was populated with a "1" or "3" respectively. Interpolated positions were then y comparison of image content against bathymetric features at corresponding s, primarily at transitions between high-relief reef and low-relief sediment. Image nage metadata records (generated in csv format) were uploaded for access and in Squidle+.	
Limitations or	n public acces	38	
Scope	dataset		
DQ Conceptua	al Consistenc	у	
Effective date	2020-05	-18	
Explanation	As the in section of seconds and hear	As the imagery is acquired using a moving platform some images may capture the same section of seabed. Survey speed of \sim 1kt (0.51m/s); image capture rate 1 image every 2 seconds; and approximate area of seabed captured in each image. nb: tow-fish roll, pitch and heave values are recorded by the video camera and saved within the video data file.	
DQ Absolute E	External Posit	ional Accuracy	
Effective date	2020-05	-18	
Explanation	Squidle+ fish' abo have an = [Wate [P-Senso whereas of USBL real-time 12.4m fo = 0). US from cer Original conventi	Squidle+ ingestion of data requires a position and an altimetry value or height of the 'tow fish' above the seabed. At the time of acquisition, the the towed video system did not have an altimeter and thus the height of the tow fish was estimated as Tow-Fish Altitude = [Water Depth at Tow-Fish (from MBES survey)] - [Tow-Fish Pressure Sensor Depth] + [P-Sensor to SLR camera (offset =0.52)] nb. P-sensor value is not corrected for tide whereas MBES data is static to AHD. XY position of fish is determined by relative position of USBL transponder (fish) to transceiver (vessel). GPS position is G2 quality (~0.4-0.5 in real-time) and is relative to the vessels Centre of Mass (reference frame 0:0:0) with a 12.4m forward offset (X = -1.5) from transceiver to COM entered in the USBL software (Y = 0). USBL heading offset is checked following each installation (nominally 23 degrees from centreline) and USBL (Tracklink, USA) precision is 3 degrees of slant range value. Original image time-stamping is synched with computer UTC (<1s) but naming convention uses USBL/Video text feed based on POS MV output.	
Responsibl	e party		
Contact pos	ition	Data Broker	
Organisatior	n name	NSW Department of Climate Change, Energy, the Environment and Water	
Telephone n	umber	131555	
Email addres	SS	data.broker@environment.nsw.gov.au	
Web address	s	https://www.nsw.gov.au/departments-and-agencies/dcceew	
Responsible	party role	pointOfContact	

Metadata point of contact			
Contact position	Data Broker		
Organisation name	NSW Department of Climate Change, Energy, the Environment and Water		
Telephone number	131555		
Email address	data.broker@environment.nsw.gov.au		
Web address	https://www.nsw.gov.au/departments-and-agencies/dcceew		
Responsible party role	pointOfContact		
Metadata date	2024-02-26T13:43:53.951309		
Metadata language			